

Y Polyester Cloth










RCK81

Ideal for middle duty sanding low alloy steel, stainless steel, high alloy steel, heat resistant steel and cast iron materials in wide belts, narrow belts, rolls, discs and velcro discs; ideal for centerless grinding. Y polyester cloth backing with resined bonder of semi open coated Compact Aluminum Oxide abrasive. Suitable for wet and dry applications.



Product Code	Abrasive Grain	Backing	Coating	Jumbo Width (mm)	Grit Range
RCK81	Compact Aluminum Oxide	Y Polyester Cloth	Semi Open	1420	80 - 1200

Grit Range																				
						80	100	120	150	180	220	240	280	320	400	500	600	800	1000	1200

Product Forms				
 Jumbo	 Segmented Belt (Multi Joint)	 Wide Belt	 Narrow Belt	 Roll
 Disc	 Velcro Disc	 Flap Wheel	 Flap Disc	

Application Areas			
Wood	Parquet / Floor Sanding	Low Alloy Steel	Stainless Steel / Inox
High Alloy Steel / Heat Resistant Steel	Aluminium / Zamak	Brass / Copper / Non Ferrous Metals	Paint / Varnish / Lacquer
Plastic / Rubber / Leather	Cast Iron	Glass / Stone / Granite / Ceramic	

Features		
Antistatic Feature	Suitable for Wet Applications	Friction & Heat Absorbant (Top Size)
Anti-Clogging (Stearate)	Flexible for Curved Surfaces	Tear Resistant