


Product Data Sheet



J Flexible Polycotton Cloth

RS737

Ideal for sanding low alloy steel, stainless steel, high alloy steel, heat resistant steel, aluminum and zamak in narrow belts and rolls. J flexible poly-cotton cloth backing with closed coated Aluminum Oxide abrasive. Also has Stearate coating for anti-clogging feature. Flexible structure, ideal for polishing.

Product Code	Abrasive Grain	Backing	Coating	Jumbo Width (mm)	Grit Range
RS737	Aluminum Oxide	J Flexible Polycotton Cloth	Stearate & Closed	1400	60 - 1000

Grit Range																			
				60	80	100	120	150	180	220	240	280	320	400	500	600	800	1000	

Product Forms				
				
Jumbo	Segmented Belt (Multi Joint)	Wide Belt	Narrow Belt	Roll
				
Disc	Velcro Disc	Flap Wheel	Flap Disc	

Application Areas			
Wood	Parquet / Floor Sanding	Low Alloy Steel	Stainless Steel / Inox
High Alloy Steel / Heat Resistant Steel	Aluminium / Zamak	Brass / Copper / Non Ferrous Metals	Paint / Varnish / Lacquer
Plastic / Rubber / Leather	Cast Iron	Glass / Stone / Granite / Ceramic	

Features		
Antistatic Feature	Suitable for Wet Applications	Friction & Heat Absorbant (Top Size)
Anti-Clogging (Stearate)	Flexible for Curved Surfaces	Tear Resistant